

Forklift Attachment

Forklift Attachments Mississippi - Many different jobs would be impossible without the help of forklift attachments. There are numerous forklift attachments that make jobs faster and safer to complete. Besides regular forklift training, operators also need to undergo proper training for every attachment they will be using. There are many non-hydraulic attachments and hydraulic attachments available for forklift attachments. They provide many benefits including decreasing fuel consumption, time, man-power, damage to stock and employee accidents. Equipment Considerations Forklift attachments can be switched out to replace existing attachments or may be used on machines that don't currently have one. Various considerations need to be taken prior to adding or replacing any forklift attachment. These considerations include the kind of forklift, the machine's capacity, the number of hydraulic functions required to power the attachment's and the type of carriage. Failing to take these aforementioned factors into consideration can create extra safety hazards and risks for the operator, the forklift, its' attachments and the stock. Further safety factors must also be taken into consideration, which will be discussed in greater detail below. Forklift Rating and Re-Rating Manufacturers give forklifts a lift capacity rating that needs to be considered and adjusted when adding or changing forklift attachments. Manufacturers of forklift attachments usually offer calculators available online to estimate the safe lifting capacity when using a particular attachment. Accurate lifting capacities are only available from the forklift manufacturers. Before installing any kind of attachment, it is essential to contact the local authorized forklift dealer of the particular forklift brand to request that they rate the machine accordingly with the attachment being used. There will be a new specification plate that is factory authorized once the forklift manufacturer has re-rated the machine. This new specification plate will replace the original plate and should be installed showing the new rating for the forklift. Equipment Upgrades Forklift attachments rely on the machine's hydraulic function and are made up of a forklift valve that has a lever situated close to the operator. This creates two passages of pressurized hydraulic oil for powering the attachment features. While not all forklift attachments are hydraulic, hydraulic attachments often include more features than the forklift has valves. In these instances, one or more valves need to be added. There are several methods of adding a valve. The manufacturers of forklifts create accessories to simplify hose and valve routing. Due to the cost of labor and parts required, this process may not be practical. Another possibility is to install a cable reel, solenoid valve and hose to divert oil from an alternate location. The main issue is that the cable reels and hose may block the view of the operator and these items can be damaged. Special hoses and a solenoid valve kit an be used to create an electrical conduit out of the reinforced braid. Since these hoses replace existing forklift hoses, they remain safe from external damage while maintaining clear vision for the operator. Safety Considerations Proper training must be obtained prior to fitting any forklift attachment. The operator needs to be able to remove, fit and operate the attachment. Before using any forklift attachment, two safety issues need consideration. Firstly, it is important to note that any kind of forklift attachment will reduce the machine's nominal load rating. The nominal load rating is computed with a stock fork carriage and forks. However, the actual load rating may be substantially lower. Second, the center of gravity will be affected by the use of any forklift attachment. Obviously, the stability of the forklift is reduced. Due to the attachment weight being situated in front of the fulcrum point, the forklift needs to be driven as though it is partially loaded even when it is empty. It is essential that operators travel slowly and make gentle turns when using any kind of forklift attachment. Every attachment should be listed on the forklift capacity data plate. Certain safety checks need to be done before using any kind of attachment. The forklift attachment must be permitted on the forklift's data plate, locked properly, correctly attached, appropriate for the particular load and appropriate for the type of forklift being used. List of Common Forklift Attachments Below is a list of popular forklift attachments and their general uses. This is just a sample list of some of the most popular forklift attachments. The variety of attachments can drastically

increase efficiency for many jobs. SIDESHIFTER: The sideshifter enables the forklift to move laterally for easier load placement without having to reposition the entire machine. FORK POSITIONERS: The fork positioners adjust for different loads by moving the forks together or apart in relation to each other. DIMENSIONING DEVICES: Dimensioning devices offer cargo dimensions to create more warehouse efficiency and better truck and trailer space. This is commonly used with billing systems that record volume. ROTATOR: A rotator helps to straighten tilted skids and handle custom load requirements and fast unloading. Numerous attachments have a rotator feature. ROLL AND BARREL CLAMP: The roll and barrel clamp simplifies grasping rounded loads such as barrels. It has numerous pressure settings for handling fragile items with less damage potential. This attachment often has a rotate function to change the load from a vertical to a horizontal position. CARTON AND MULTIPURPOSE CLAMP: Allows for grasping a load with a more squared shape, often with pressure settings. Products like cartons, boxes and bales can be moved with this type of attachment. POLE ATTACHMENTS: Long, metal pole used in place of forks to lift rolled items such as carpet or linoleum. SLIP SHEETER OR PUSH-PULL: The slip sheeter or push-pull allows the operator to move sheets by clamping onto slip sheets. This is an option instead of relying on pallets. The slip sheet can be moved onto thin and wide metal forks to simplify loading or unloading by pushing the slip sheet. The "Save" variation allows the slip sheet to be taken off for reuse later. The "Standard," attachment variation is another option. DRUM HANDLER: The drum handler is specifically designed to transport drums. It might feature arms to hold the drum or be a spring-loaded model to grip the top lid. DRUM AND STORAGE BIN TIPPER: Allows for quick transfer of loose or liquid contents in large containers. MAN BASKET: The lift platform known as a man basket is designed to transport workers vertically. It is outfitted with brackets and railings to anchor safety harnesses. TELESCOPIC FORKS: The telescopic forks are used in locations with a two pallet stacking design were one shelf is placed right behind another with no aisle between them. SCALES: Enables operators to simultaneously weigh and transport pallets, eliminating the need to interrupt transport to travel to scales, and can be obtained in legal-for-trade weights for operations that bill by weight. SINGLE-DOUBLE FORKS: Allow movement of a single pallet or platform or two pallets side by side. With the correct attachment/s a single forklift can be used for multiple specialist materials handling tasks alongside normal lifting tasks, thus reducing the need for owning a specialist unit alongside a normal unit and the larger running and maintenance costs associated with multiple units. SNOW PLOW: Designed for snow removal and distribution but can also be used to move other types of loose material. SKIPS: Allows safe and speedy removal of waste to the appropriate skip or waste compactor. Skips are available in a roll-forward type and a bottom-emptying type. BOOMS AND JIBS: Booms and jibs allow forklifts extended reach. They are available to transport deep or highly stacked loads, suspended loads and more. These attachments can be low profile, precision lifting or reach over models to facilitate extended lengths.